


ABSORPTION

ABSORBEL S PE-ALU – sound absorbing foam with top layer



ABSORBEL	Colour	Thickness
S 13 PE-ALU	black	13 mm
S 15 PE-ALU	black	15 mm
S 20 PE-ALU	black	20 mm
S 25 PE-ALU	black	25 mm
S 30 PE-ALU	black	30 mm
S 40 PE-ALU	black	40 mm
S 50 PE-ALU	black	50 mm
S = Selfadhesive		

Description	Absorbel S PE-ALU is an open cell polyurethane foam with strong and decorative PE aluminium colored protective top layer. Absorbel S PE-ALU is suitable for indoor use.
Characteristics	<ul style="list-style-type: none"> • Very good noise absorption properties, for higher frequencies as well • Flame retardant in accordance with DIN 53438, MVSS 302 • Easy to cut with a (Stanley) knife, with scissors or to saw with a band saw • Protective layer is resistant to splashing, oil, petrol and prevents penetration of fluids and vapours into the foam • Resistant to ageing • Temperature resistant from -30 to 90 °C
Application	Automotive industry, yacht and ship building, housing, electrical appliances, Machine building, cabin construction
Processing	Surface must be clean, dry and dust and grease free Do not process sheets at temperatures below 10 °C We recommend taping the seams with ABSORBEL TAPE black if there is a risk of moisture or vapours penetrating through the seams of the sheets
Sizes	Sheets of 1000 x 1400 mm ABSORBEL PE-ALU TAPE: 50 mm width For weights and thicknesses see table above Dye-cut to size parts available